



Table #1.
**Aluminium Alloyed
Flush Mounted
Anodes**




Type	A (mm)	B (mm)	C (mm)	D (mm)	Insert (mm)	NWT (kg)t	GWT (kg)
W131	300	200	95	32	20x3	1.2	1.3
W130	350	270	150	32	40x6	2.6	3.2
W111	500	400	150	32	40x6	4.0	5.0
W114	650	550	130	50	40x6	8.0	9.2
W117	650	550	130	65	50x6	10.1	11.6
W119	650	550	130	75	50x6	12.6	14.1
W118	650	550	130	95	50x6	16.5	18.0
W124	1015	920	130	50	50x6	13.0	15.4
W126	1015	920	130	75	50x6	21.0	23.4
W128	1015	920	130	105	50x6	30.0	32.4

Table #3.
**Zinc Alloyed
Flush Mounted
Anodes**




Type	A (mm)	B (mm)	C (mm)	D (mm)	Insert (mm)	NWT (kg)t	GWT (kg)
WP3	300	200	95	30	40x3	3.1	3.2
W6Z	350	270	150	32	40x6	6.5	7.1
W11Z	500	400	150	32	40x6	10.8	11.8
W14Z	650	550	130	50	40x6	21.3	22.5
W17Z	650	550	130	65	50x6	25.0	26.5
W18Z	650	550	130	95	50x6	42.6	44.1
W19Z	650	550	130	75	50x6	33.0	34.5
W24Z	1015	920	130	50	50x6	35.0	37.4

Table #4.
**Zinc Alloyed
Flush Mounted
Anodes
(drop shape)**




Type	A (mm)	B (mm)	C (mm)	D (mm)	Insert (mm)	NWT (kg)t	GWT (kg)
WP1	260	180	60	32	20x3	1.0	1.1
WP2	300	220	75	38	20x3	2.15	2.3
WP5	380	290	100	50	30x5	4.55	5.0
W10Z	400	280	150	75	40x6	10.0	10.7
W16Z	520	420	160	70	40x6	15.0	16.0

Table #6.
**“C” Clamp Mounted
Slender Stand-Off
Anodes
(Pit Guard)**




Type	Alloy	A (mm)	B (mm)	C (mm)	F Dia. (mm)	NWT (kg)
AT2235	Aluminium	193	70	76	2.25	2.25
AT2235/1	Aluminium	386	70	76	4.5	4.5
AT2235/2	Aluminium	344	70	76	4.0	4.0
ZT2247	Zinc	332	70	76	10.0	10.0

Table #7.
**Standard Bolted
Anodes**




Type	A (mm)	B (mm)	C (mm)	D (mm)	F (mm)	Aluminum Alloy	Zinc Alloy
						GWT (kg)	GWT (kg)
B4	200	100	40	110	50	1.8	4.20
B9E	300	150	40	160	50	4.6	11.0
B9F	300	150	50	160	50	5.5	13.8
B9H	300	150	60	160	50	6.5	16.5
B9G	300	150	65	160	50	7.0	18.0
B12E	300	200	40	160	50	6.6	15.2
B12F	300	200	50	160	50	7.5	18.8
B12H	300	200	60	160	50	9.7	25.0
B12G	300	200	65	160	50	10.7	26.8

Table #8.
**Aluminium Alloyed
Bolted Anodes**



Type	A (mm)	B (mm)	C (mm)	D (mm)	F (mm)	NWT (kg)	GWT (kg)
MF 134 E	400	180	40	180	50	7.4	7.8
MF 134 F	400	180	50	180	50	9.3	9.7
MF 134 H	400	180	60	180	50	11.2	11.6
MF 134	400	180	70	180	50	13.0	13.4

Table #9.
**Aluminium Alloyed
Bolted Anodes**



Type	A (mm)	B (mm)	C (mm)	D (mm)	F (mm)	NWT (kg)	GWT (kg)
RF-118	460	200	64	260	50	11.5	11.8
RF-155	540	200	65	340	50	15.1	15.4